



SAFETY DATA SHEET

SDS No. 60A

Revision Date: January 2, 2021 Version 3.0

GHS Compliant

Section 1 - Identification of the substance/mixture and of the company

1.1 Product Identifier

Trade Name: Cryptolyte®

1.2 Relevant identified uses of the substance or mixture and uses advised against

General Use: Additive

Restrictions on Use: None known

1.3 Details of the supplier of the safety data sheet:

Company: Smooth-On, Inc.
5600 Lower Macungie Rd., Macungie, PA 18062

Telephone: Domestic: 1 (877) 706-5303
International: (610) 252-5800 (collect calls accepted)

E-mail address: Visit our website at www.smooth-on.com or email
www.sds@smooth-on.com

1.4 Emergency Contact: Chem-Tel Domestic: 800-255-3924 International: 813-248-0585

Section 2 – Hazard(s) Identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200 (OSHA HCS)

H225 Flammable liquids – Category 2

H315 Skin irritation – Category 2

H361 Reproductive toxicity – Category 2

H336 Specific target organ toxicity – single exposure – Category 3 (central nervous system)

H373 Specific target organ toxicity – repeated exposure – Category 2

H304 Aspiration hazard – Category 1

H401 Acute aquatic toxicity – Category 2

2.2 GHS Label elements, including precautionary statements



Pictogram(s)

Signal word: Danger

Physical Hazards

H225 Highly flammable liquid and vapor

Health Hazards

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation

H336 May cause drowsiness or dizziness

H361 Suspected of damaging fertility or the unborn child.

H373	May cause damage to organs.
Environmental Hazards	
H401	Toxic to aquatic life
General Precautions	
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
Prevention Precautions	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
Response Precautions	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage Precautions	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
Disposal Precautions	
P501	Dispose of contents/container according to local, state and federal laws.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

This product contains a chemical known to be hazardous according to California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). (See also Section 3 and 15).

Section 3 - Composition / Information on Ingredients

3.1 Substances/Mixtures

The following ingredients are hazardous according to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR 1910.1200:

Chemical name	CAS-No.	Concentration (% w/w)
Toluene	108-88-3	>90%

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact

Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact

In case of skin contact, wash thoroughly with soap and water.

Ingestion

Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed.

None known.

4.3 Indication of any immediate medical attention and specific treatment needed.

None known.

Section 5 - Fire-Fighting Measures

5.1 Extinguishing Media

Water Fog, Dry Chemical, and Carbon Dioxide Foam

5.2 Special hazards arising from the substance or mixture

None known.

5.3 Advice for firefighters

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full-face piece operated in pressure demand or positive-pressure mode.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Only properly protected personnel should remain in the spill area; dike and contain spill. Stop or reduce discharge if it can be done safely.

6.2 Environmental precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains or unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Put on appropriate protective gear including NIOSH/MSHA approved self-contained breathing apparatus, rubber boots and heavy rubber gloves. Dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely. Follow applicable OSHA regulations (29 CFR 1910.120) for disposal.

6.4 Reference to other sections

See Section 3 for list of Hazardous Ingredients; Sections 8 for Exposure Controls; and Section 13 for Disposal.

Section 7 - Handling and Storage**7.1 Precautions for safe handling**

Use good general housekeeping procedures. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices.

7.2 Conditions for safe storage, including any incompatibilities

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet local standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.

7.3 Specific end use(s)

These precautions are for room temperature handling. Other uses including elevated temperatures or aerosol/spray applications may require added precautions.

Section 8 - Exposure Controls / Personal Protection**8.1 Control parameters****Components with workplace control parameters**

Component	CAS-No.	Value	Control Parameters	Basis
Toluene	108-88-3	TWA	100 ppm (375 mg/m ³)	OSHA – Table Z1
		STEL	150 ppm (560 mg/m ³)	
		TWA	200 ppm	OSHA – Table Z2
		CEIL	300 ppm	
		Peak	500 ppm	
		TLV	20 ppm	ACGIH
		TWA	100 ppm (375 mg/m ³)	NIOSH
		ST	150 ppm (560 mg/m ³)	

8.2 Exposure controls**Respiratory Protection**

Respiratory protection is not normally required when using this product with adequate local exhaust ventilation. Where risk assessment shows air-purifying respirators are appropriate, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with appropriate filter cartridges as a backup to engineering controls.

Hand Protection

Wear any liquid-tight gloves such as butyl rubber, neoprene or PVC.

Eye Protection

Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Other Protective Clothing/Equipment

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

Comments

Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

Section 9 - Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	liquid	Vapor pressure:	21.8 mmHg @ 68 °F
Odor:	aromatic	Vapor density (Air=1):	No data available
pH:	No data	Evaporation rate:	No data
Flash Point:	39.2 °F	Solubility in water:	0.5 g/l @ 59 °F
Melting / freezing point:	-135 °F	Specific Gravity (H₂O=1, at 4 °C):	0.86
Low / high boiling point:	230 – 232 °F	Relative density:	No data
Upper flammability limits:	No data	Decomposition temperature:	No data
Lower flammability limits:	No data	Auto-ignition temperature:	995.0 °F
		Viscosity:	<100 centipoise

Section 10 - Stability and Reactivity

10.1 Reactivity

No hazardous reactions if stored and handled as prescribed/indicated., No corrosive effect on metal. Not fire propagating.

10.2 Chemical stability

These products are stable at room temperature in closed containers under normal storage and handling conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerization cannot occur

10.4 Conditions to avoid

None known

10.5 Incompatible materials

Strong bases and acids

10.6 Hazardous decomposition products

Thermal oxidative decomposition can produce carbon oxides, gasses/vapors, and traces of incompletely burned carbon compounds.

Section 11- Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity

LD50 Oral - > 5,000 mg/kg (rat)
LC50 Inhalation – 12.5 – 28.8 mg/l (rat)
LD50 Dermal - >5,000 mg/kg (rat)

Skin Corrosion/Irritation

Causes skin irritation (rabbit, 24 h)

Serious Eye Damage/Irritation

No eye irritation (rabbit, OECD TG 405)

Respiratory/Skin Sensitization

No data

Germ Cell Mutagenicity

No data available

Carcinogenicity

No component of these products present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC, ACGIH or NTP.

Reproductive Toxicity

Damage to fetus possible, suspected human reproductive toxicant.

Specific Target Organ Toxicity – Single Exposure

No data

Specific Target Organ Toxicity – Repeated Exposure

No data

Aspiration Hazard

No data

Chronic Exposure

No data

Potential Health Effects – Miscellaneous

No data

Section 12 - Ecological Information

12.1 Toxicity

LC50 Oncorhynchus mykiss (rainbow trout) – 8.03 mg/l (96 h)
NOEC Pimephales promelas (fathead minnow) – 5.73 mg/l (7 d)
EC50 Daphnia magna (water flea) – 8.42 mg/l (24 h)
EC50 Chlorella vulgaris (fresh water algae) – 257.9 mg/l (24 h)
EC50 Pseudokirchneriella subcapitata (green algae) – 10.5 mg/l (24 h)

12.2 Persistence and Degradability

No data available

12.3 Bioaccumulative Potential

Leuciscus idus (golden orfe) – 0.05 mg/l (3 d)

Bioconcentration factor (BCF): 90

12.4 Mobility in Soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other Adverse Effects

No data available

Section 13 - Disposal Considerations**13.1 Waste treatment methods**

Under Resource Conservation and Recovery Act (RCRA) it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste as defined in 40 CFR Part 261. Waste management should be in full compliance with federal, state and local laws. Regulations may vary in various locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator.

Container disposal

Steel drums must be emptied and can be sent to a licensed drum reconditioner for reuse, a scrap metal dealer or an approved landfill. Do not attempt to refill or clean containers since residue is difficult to remove. Under no circumstances should empty drums be burned or cut open with gas or electric torch as toxic decomposition products may be liberated. Do not reuse empty containers

Section 14 - Transport Information

Regulated by DOT, IATA or IMDG

	<i>Land transport (DOT)</i>	<i>Sea transport (IMDG)</i>	<i>Air transport (ICAO/IATA)</i>
UN number:	1294	1294	1294
UN proper shipping name:	Toluene	Toluene	Toluene
Transport hazard class(s):	3	3	3
Packing group:	II	II	II
Environmental hazards:	-	-	-
Special precautions for user:	N/A	N/A	N/A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	N/A	N/A	N/A

Section 15 - Regulatory Information**15.1 Safety health and environmental regulations/legislation specific for the substance or mixture**

REACH: Regulation (EC) No 1907/2006 of The European Parliament and of The Council of December 2006 (including amendments and corrigenda as of 17 February 2016)

This product complies with REACH or is not subject to regulation under REACH. The product does not contain an ingredient listed on either the Candidate List or Authorization List for Substances of Very High Concern (SVHC).

In the United States (EPA Regulations)

TSCA Inventory Status (40 CFR710)

All components of this formulation are listed in the TSCA Inventory. No component of this formulation has been determined to be subject to manufacturing or use restrictions under the Significant New Use Rules (SNURs).

CERCLA Hazardous Substance List (40 CFR 302.4)

None known.

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute), Delayed (Chronic), Fire

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

Component

Toluene

CAS-No.

108-88-3

Concentration(% w/w)

>90%

KEEP OUT OF REACH OF CHILDREN




WARNING: This product can expose you to chemicals including Toluene (CAS 108-88-3), which is known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

15.2 Chemical safety assessment

No chemical safety assessment has been carried out for this substance/mixture by the supplier.

16 - Other Information

HMIS	
H	2
F	3
R	0



NFPA

Revision Date: January 2, 2021 Version 3.0

Abbreviations and acronyms

ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance

Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals; HMIS-Hazardous Material Information Service; IATA-International Air Transport Association; IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

Disclaimer

The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Buddy Rhodes Concrete Products, it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.

This SDS is prepared to comply with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) as prescribed by the United States (US) Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS), and European Union Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 (REACH).

Classifications of the chemical in accordance with 29 CFR 1910.1200, signal word, hazard and precautionary statement(s), symbol(s) and other information are based on listed concentration of each hazardous ingredient. Unlisted ingredients are not "hazardous" per the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS and EC No 1907/2006 and are considered trade secrets under US Federal Law (29 CFR and 40 CFR), Canadian Law (Health Canada Legislation), and European Union Directives.