



Part A: URE-BOND II (SDS No. 90A)

Part B: URE-BOND II (SDS No. 90B)

SAFETY DATA SHEET

SDS No. 90A

Revision Date: January 2, 2021 Version 3.0

GHS Compliant

Section 1 - Identification of the substance/mixture and of the company

1.1 Product Identifier

Trade Name: **URE-BOND® II Part A**

1.2 Relevant identified uses of the substance or mixture and uses advised against

General Use: Formulated Polyurethane Isocyanate

Restrictions on Use: None known

1.3 Details of the supplier of the safety data sheet:

Company: Smooth-On, Inc.,
5600 Lower Macungie Rd., Macungie, PA 18062
Telephone: Phone (610) 252-5800

E-mail address: Visit our website at www.smooth-on.com or email
www.sds@smooth-on.com

1.4 **Emergency Contact:** Chem-Tel Domestic: 800-255-3924 International: 813-248-0585

Section 2 – Hazard(s) Identification

2.1 Classification of the substance or mixture:

GHS Classification in accordance with 29 CFR 1910.1200 (OSHA HCS)

H315 Skin Irritation – Category 2

H317 Skin Sensitization – Category 1

H320 Eye Irritation – Category 2B

H332 Acute Toxicity, Inhalation – Category 4

H334 Respiratory Sensitization – Category 1

H335 Specific Target Organ Toxicity (Single Exposure) – Category 3 (respiratory)

2.2 GHS Label elements, including precautionary statements



Pictogram(s):

Signal word: Danger

Health Hazards:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H320 Causes eye irritation

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation

General Precautions:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

Prevention Precautions:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	In case of inadequate ventilation wear respiratory protection.

Response Precautions:

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P342+P311	IF experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Storage Precautions:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Disposal Precautions:

P501 Dispose of contents/container according to local, state and federal laws.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS – none known**Section 3 - Composition / Information on Ingredients****3.1 Substances/Mixtures**

The following ingredients are hazardous according to Regulation 2012 OSHA Hazard Communication Standard: 29 CFR 1910.1200:

Chemical name	CAS-No.	Concentration
Diphenylmethane Diisocyanate, isomers and homologues	9016-87-9	20 – 35
4,4' -Methylenediphenyl diisocyanate	101-68-8	10 – 20

Section 4 - First Aid Measures**4.1 Description of first aid measures****Inhalation**

Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact

Flush eyes with plenty of water occasionally lifting the upper and lower eyelids. Check and remove any contact lenses if safe to do so. Continue to rinse for at least 15 minutes. If irritation develops, seek medical attention.

Skin Contact

In case of skin contact, wash thoroughly with soap and water. Continue to rinse for at least 15 minutes. Chemical burns must be treated promptly by a physician.

Ingestion

Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

4.2 Most important symptoms and effects, both acute and delayed

In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

4.3 Indication of any immediate medical attention and specific treatment needed.

None known.

Section 5 - Fire-Fighting Measures

5.1 Extinguishing Media

Water Fog, Dry Chemical, and Carbon Dioxide Foam

5.2 Special hazards arising from the substance or mixture

In a fire or if heated, a pressure increase will occur, and the container may burst.

5.3 Advice for firefighters

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full-face piece operated in pressure demand or positive-pressure mode.

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Only properly protected personnel should remain in the spill area; dike and contain spill. Stop or reduce discharge if it can be done safely.

6.2 Environmental precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains or unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Put on appropriate protective gear including NIOSH/MSHA approved self-contained breathing apparatus, rubber boots and heavy rubber gloves. Dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely. Follow applicable OSHA regulations (29 CFR 1910.120) for disposal.

6.4 Reference to other sections

See Section 3 for list of Hazardous Ingredients; Sections 8 for Exposure Controls; and Section 13 for Disposal.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Use good general housekeeping procedures. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices.

7.2 Conditions for safe storage, including any incompatibilities

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet local standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.

7.3 Specific end use(s)

These precautions are for room temperature handling. Other uses including elevated temperatures or aerosol/spray applications may require added precautions.

Section 8 - Exposure Controls / Personal Protection

8.1 Control parameters

Components with workplace control parameters

Component	CAS-No.	Value	Control Parameters	Basis
Diphenylmethane-4,4'-diisocyanate	101-68-8	TWA	0.0050 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Respiratory sensitization		
		C	0.02 ppm 0.2 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		C	0.02 ppm 0.2 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		The value in mg/m ³ is approximate. Ceiling limit is to be determined from breathing-zone air samples.		
		TWA	0.0050 ppm 0.05 mg/m ³	USA. NIOSH Recommended Exposure Limits
		10 minute ceiling value		
		C	0.2 ppm 0.2 mg/m ³	USA. NIOSH Recommended Exposure Limits
		10 minute ceiling value		

8.2 Exposure controls

Respiratory Protection

Respiratory protection is not normally required when using this product with adequate local exhaust ventilation. Where risk assessment shows air-purifying respirators are appropriate, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with appropriate filter cartridges as a backup to engineering controls.

Hand Protection

Wear any liquid-tight gloves such as butyl rubber, neoprene or PVC.

Eye Protection

Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Other Protective Clothing/Equipment

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

Comments

Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

Section 9 - Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance:	Brown liquid	Vapor pressure:	0.00016 mmHg (68 °F)
Odor:	Slight	Vapor density (Air=1):	8.6
pH:	No data	Evaporation rate:	No data
Flash Point:	390°F	Solubility in water:	Insoluble
Melting / freezing point:	37°F	Specific Gravity (H2O=1, at 4 °C):	No data
Low / high boiling point:	No data	Relative density:	No data
Upper flammability limits:	No data	Decomposition temperature:	No data
Lower flammability limits:	No data	Viscosity:	100 centipoise

Section 10 - Stability and Reactivity
--

10.1 Reactivity

No hazardous reactions if stored and handled as prescribed/indicated., No corrosive effect on metal. Not fire propagating.

10.2 Chemical stability

These products are stable at room temperature in closed containers under normal storage and handling conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerization cannot occur

10.4 Conditions to avoid

None known

10.5 Incompatible materials

Strong bases and acids

10.6 Hazardous decomposition products

Thermal oxidative decomposition can produce carbon oxides, gasses/vapors, and traces of incompletely burned carbon compounds.

Section 11- Toxicological Information**11.1 Information on toxicological effects****Acute Toxicity****Acute inhalation toxicity**

At room temperature, vapors are minimal due to low volatility. However, certain operations may generate vapor or mist concentrations sufficient to cause respiratory irritation and other adverse effects. Such operations include those in which the material is heated, sprayed or otherwise mechanically dispersed such as drumming, venting or pumping. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. May cause pulmonary edema (fluid in the lungs.) Effects may be delayed. Decreased lung function has been associated with overexposure to isocyanates.

LC50, Rat, 4 Hour, dust/mist, 0.49 mg/l

For similar material(s): 4,4'-Methylenediphenyl diisocyanate (CAS 101-68-8).

LC50, Rat, 1 Hour, Aerosol, 2.24 mg/l

For similar material(s): 2,4'-Diphenylmethane diisocyanate (CAS 5873-54-1).

LC50, Rat, 4 Hour, Aerosol, 0.387 mg/l

Skin Corrosion/Irritation

Prolonged contact may cause slight skin irritation with local redness. May stain skin.

Serious Eye Damage/Irritation

May cause moderate eye irritation. May cause slight temporary corneal injury.

Respiratory/Skin Sensitization

Skin contact may cause an allergic skin reaction. Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization. May cause allergic respiratory reaction. Reexposure to extremely low isocyanate concentrations may cause allergic respiratory reactions in individuals already sensitized. Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening. Effects may be delayed.

Germ Cell Mutagenicity

No data available

Carcinogenicity

Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m³) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.

Reproductive Toxicity

No data available

Specific Target Organ Toxicity – Single Exposure

May cause respiratory irritation. Route of Exposure: Inhalation Target Organs: Respiratory Tract

Specific Target Organ Toxicity – Repeated Exposure

Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

Potential Health Effects – Miscellaneous

No data available

Section 12 - Ecological Information
12.1 Toxicity**Acute toxicity to fish**

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species.

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Danio rerio (zebra fish), static test, 96 Hour, > 1,000 mg/l, OECD Test Guideline 203 or Equivalent

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 24 Hour, > 1,000 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

NOEC, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, 1,640 mg/l, OECD Test Guideline 201 or Equivalent

12.2 Persistence and Degradability:

Biodegradability: In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates. 10-day Window: Not applicable

Biodegradation: 0 %

Exposure time: 28 d

Method: OECD Test Guideline 302C or Equivalent

12.3 Bioaccumulative Potential

Bioconcentration factor (BCF): 92 Cyprinus carpio (Carp) 28 d

Diphenylmethane Diisocyanate, isomers and homologues

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3). Reacts with water. In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Bioconcentration factor (BCF): 92 Cyprinus carpio (Carp) 28 d

4,4' -Methylenediphenyl diisocyanate

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3). Reacts with water. In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Bioconcentration factor (BCF): 92 Cyprinus carpio (Carp) 28 d

12.4 Mobility in Soil

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other Adverse Effects

No data available

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Under Resource Conservation and Recovery Act (RCRA) it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste as defined in 40 CFR Part 261. Waste management should be in full compliance with federal, state and local laws. Empty containers retain product residue which may exhibit hazards of material, therefore to not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Section 14 - Transport Information

Not regulated by DOT / IMDG / IATA

Section 15 - Regulatory Information

15.1 Safety health and environmental regulations/legislation specific for the substance or mixture:

REACH: Regulation (EC) No 1907/2006 of The European Parliament and of The Council of December 2006 (including amendments and corrigenda as of 17 February 2016)

This product complies with REACH or is not subject to regulation under REACH. The product does not contain an ingredient listed on either the Candidate List or Authorization List for Substances of Very High Concern (SVHC).

In the United States (EPA Regulations)

TSCA Inventory Status (40 CFR710)

All components of this formulation are listed in the TSCA Inventory. No component of this formulation has been determined to be subject to manufacturing or use restrictions under the Significant New Use Rules (SNURs).

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

Components

	CAS#	RQ
4,4'-Methylenediphenyl diisocyanate	101-68-8	5000 lbs RQ

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute), Delayed (Chronic), Fire

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This product contains the following substances which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and which are listed in 40 CFR 372.

Components

44' -Methylenediphenyl diisocyanate
Diphenylmethane Diisocyanate, isomers and homologues

CASR#

101-68-8
9016-87-9

California Proposition 65


This product does not intentionally contain any chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

15.2 Chemical safety assessment

No chemical safety assessment has been carried out for this substance/mixture by the supplier.

16 - Other Information

HMIS	
H	2
F	1
R	1

**NFPA**

Revision Date: January 2, 2021 Version 3.0

Abbreviations and acronyms

ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals; HMIS-Hazardous Material Information Service; IATA-International Air Transport Association; IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

Disclaimer

The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.



Part A: URE-BOND II (SDS No. 90A)

Part B: URE-BOND II (SDS No. 90B)

SAFETY DATA SHEET

SDS No. 90B

Revision Date: January 2, 2021 Version 2.0

GHS Compliant

Section 1 - Identification of the substance/mixture and of the company

1.1 Product Identifier

Trade Name: **URE-BOND® II Part B**

1.2 Relevant identified uses of the substance or mixture and uses advised against

General Use: Formulated Polyurethane Isocyanate

Restrictions on Use: None known

1.3 Details of the supplier of the safety data sheet:

Company: Smooth-On, Inc.,
5600 Lower Macungie Rd., Macungie, PA 18062

Telephone: Phone (610) 252-5800

E-mail address: Visit our website at www.smooth-on.com or email
www.sds@smooth-on.com

1.4 **Emergency Contact:** Chem-Tel Domestic: 800-255-3924 International: 813-248-0585

Section 2 – Hazard(s) Identification

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture according to United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200), the Canadian Workplace Hazardous Materials Information System (WHMIS) and Regulation (EC) No 1272/2008 and subsequent amendments.

2.2 GHS Label elements, including precautionary statements

Pictogram(s): none

Signal word: none

General Precautions:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

2.3 **Hazards not otherwise classified (HNOC) or not covered by GHS – none**

Section 3 - Composition / Information on Ingredients

3.1 Substances

No ingredients are hazardous according to Regulation 2012 OSHA Hazard Communication Standard 29 CFR 1910.1200 criteria.

Section 4 - First Aid Measures

4.1 Description of first aid measures

Inhalation

Remove source(s) of contamination and move victim to fresh air. If breathing has stopped, give artificial respiration, then oxygen if needed. Contact physician immediately.

Eye Contact

Flush eyes with plenty of water. If irritation persists, seek medical attention.

Skin Contact

In case of skin contact, wash thoroughly with soap and water.

Ingestion

Do not induce vomiting unless instructed by a physician. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and specific treatment needed.

None known.

Section 5 - Fire-Fighting Measures**5.1 Extinguishing Media**

Water Fog, Dry Chemical, and Carbon Dioxide Foam

5.2 Special hazards arising from the substance or mixture

None known.

5.3 Advice for firefighters

Use water spray to cool fire-exposed surfaces and to protect personnel. Shut off "fuel" to fire. If a leak or spill has not ignited, use water spray to disperse the vapors. Either allow fire to burn under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full-face piece operated in pressure demand or positive-pressure mode.

Section 6 - Accidental Release Measures**6.1 Personal precautions, protective equipment and emergency procedures**

Only properly protected personnel should remain in the spill area; dike and contain spill. Stop or reduce discharge if it can be done safely.

6.2 Environmental precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains or unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers. No special environmental precautions required.

6.3 Methods and material for containment and cleaning up

Put on appropriate protective gear including NIOSH/MSHA approved self-contained breathing apparatus, rubber boots and heavy rubber gloves. Dike and contain spill; absorb or scrape up excess into suitable container for disposal; wash area with dilute ammonia solution. Stop or reduce discharge if it can be done safely. Follow applicable OSHA regulations (29 CFR 1910.120) for disposal.

6.4 Reference to other sections

See Section 3 for list of Hazardous Ingredients; Sections 8 for Exposure Controls; and Section 13 for Disposal.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Use good general housekeeping procedures. Wash hands after use. Do not get in eyes, on skin or on clothing. Do not breathe vapors or mists. Use good personal hygiene practices.

7.2 Conditions for safe storage, including any incompatibilities

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well ventilated place away from heat, direct sunlight, strong oxidizers and any incompatibles. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet local standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Avoid water contamination.

7.3 Specific end use(s)

These precautions are for room temperature handling. Other uses including elevated temperatures or aerosol/spray applications may require added precautions.

Section 8 - Exposure Controls / Personal Protection

8.1 Control parameters

None defined

8.2 Exposure controls

Respiratory Protection

Respiratory protection is not normally required when using this product with adequate local exhaust ventilation. Where risk assessment shows air-purifying respirators are appropriate, follow OSHA respirator regulations 29 CFR 1910.134 and European Standards EN 141, 143 and 371; wear an MSHA/NIOSH or European Standards EN 141, 143 and 371 approved respirators equipped with appropriate filter cartridges as a backup to engineering controls.

Hand Protection

Wear any liquid-tight gloves such as butyl rubber, neoprene or PVC.

Eye Protection

Safety glasses with side shields per OSHA eye- and face-protection regulations 29 CFR 1910.133 and European Standard EN166. Contact lenses are not eye protective devices. Appropriate eye protection must be worn instead of, or in conjunction with contact lenses.

Other Protective Clothing/Equipment

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

Comments

Never eat, drink, or smoke in work areas. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. Wash thoroughly after handling.

Section 9 - Physical and Chemical Properties

9.1 Information on basic physical and chemical properties:

Appearance:	Viscous liquid	Vapor pressure:	No data
Odor:	Slight	Vapor density (Air=1):	>1

pH:	No data	Evaporation rate:	No data
Flash Point:	300°F	Solubility in water:	Insoluble
Melting / freezing point:	No data	Specific Gravity (H₂O=1, at 4 °C):	1.07
Low / high boiling point:	No data	Relative density:	No data
Upper flammability limits:	No data	Decomposition temperature:	No data
Lower flammability limits:	No data	Viscosity:	>20,000 centipoise

Section 10 - Stability and Reactivity

10.1 Reactivity

No hazardous reactions if stored and handled as prescribed/indicated., No corrosive effect on metal. Not fire propagating.

10.2 Chemical stability

These products are stable at room temperature in closed containers under normal storage and handling conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerization cannot occur

10.4 Conditions to avoid

None known

10.5 Incompatible materials

Strong bases and acids

10.6 Hazardous decomposition products

Thermal oxidative decomposition can produce carbon oxides, gasses/vapors, and traces of incompletely burned carbon compounds.

Section 11- Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity

No data available

Skin Corrosion/Irritation

No data available

Serious Eye Damage/Irritation

No data available

Respiratory/Skin Sensitization

No data available

Germ Cell Mutagenicity

No data available

Carcinogenicity

No component of these products present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by IARC, ACGIH or NTP.

Reproductive Toxicity

No data available

Specific Target Organ Toxicity – Single Exposure

No data available

Specific Target Organ Toxicity – Repeated Exposure

No data available

Aspiration Hazard

No data available

Potential Health Effects – Miscellaneous

No data available

Section 12 - Ecological Information**12.1 Toxicity**

No data available

12.2 Persistence and Degradability

No data available

12.3 Bioaccumulative Potential

No data available

12.4 Mobility in Soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Other Adverse Effects

No data available

Section 13 - Disposal Considerations**13.1 Waste treatment methods**

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty containers retain product residue which may exhibit hazards of material, therefore to not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

Section 14 - Transport Information**Not regulated by DOT / IMDG / IATA****Section 15 - Regulatory Information****15.1 Safety health and environmental regulations/legislation specific for the substance or mixture:**

REACH: Regulation (EC) No 1907/2006 of The European Parliament and of The Council of December 2006 (including amendments and corrigenda as of 17 February 2016)

This product complies with REACH or is not subject to regulation under REACH. The product does not contain an ingredient listed on either the Candidate List or Authorization List for Substances of Very High Concern (SVHC).

In the United States (EPA Regulations)**TSCA Inventory Status (40 CFR710)**

All components of this formulation are listed in the TSCA Inventory. No component of this formulation has been determined to be subject to manufacturing or use restrictions under the Significant New Use Rules (SNURs).

CERCLA Hazardous Substance List (40 CFR 302.4)

None known.

SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

None known.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and community Right-to-Know Act of 1986) Sections 311 and 312

None

California Proposition 65


This product does not intentionally contain any chemicals known to the state of California to cause cancer, birth defects or other reproductive harm.

15.2 Chemical safety assessment

No chemical safety assessment has been carried out for this substance/mixture by the supplier.

16 - Other Information

HMIS	
H	1
F	0
R	0



NFPA

Abbreviations and acronyms

Revision Date: January 2, 2021 Version 2.0

ACGIH-American Conference of Governmental Industrial Hygienists; ANSI-American National Standards Institute; Canadian TDG-Canadian Transportation of Dangerous Goods; CAS-Chemical Abstract Service; Chemtrec-Chemical Transportation Emergency Center (US); CHIP-Chemical Hazard Information and Packaging; DSL-Domestic Substances List; EC-Equivalent Concentration; EH40 (UK)-HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA-Emergency Planning and Community Right-To-Know Act; ESL-Effects screening levels; GHS-Globally Harmonized System of Classification and Labelling of Chemicals; HMIS-Hazardous Material Information Service; IATA-International Air Transport Association; IMDG-International Maritime Dangerous Goods Code; LC-Lethal Concentration; LD-Lethal Dose; LEL-Lower Explosion Level; NFPA-National Fire Protection Association; OEL-Occupational Exposure Limit; OSHA-Occupational Safety and Health Administration, US Dept. of Labor; PEL-Permissible Exposure Limit; SARA (Title III)-Superfund Amendments and Reauthorization Act; SARA 313-Superfund Amendments and Reauthorization Act, Section 313; SCBA-Self-Contained Breathing Apparatus; STEL-Short Term Exposure Limit; TCEQ-Texas Commission on Environmental Quality; TLV-Threshold Limit Value; TSCA-Toxic Substances Control Act Public Law 94-469; TWA-Time Weighted Value; UEL-Upper Explosion Level; US DOT-US Department of Transportation; WHMIS-Workplace Hazardous Materials Information System.

Disclaimer

The information contained in this Safety Data Sheet (SDS) is considered accurate as of the version date. However, no warranty is expressed or implied regarding the accuracy of the data. Since the use of this product is not within the control of Smooth-On Inc., it is the user's obligation to determine the suitability of the product for its intended application and assumes all risk and liability for its safe use.